

WE ARE TRANSFORMING MOBILITY THANKS TO A BLEND OF TECHNOLOGY AND ART, A COMBINATION OF NEW IDEAS AND UNIQUE DESIGN. WE ARE SHOWING THE WHOLE WORLD THAT FUNCTIONALITY CAN BE FUN AND THAT PRACTICALITY CAN ALSO BE A THING OF BEAUTY. AS YOU FLICK THE IGNITION SWITCH, WE WANT IT TO SET

OFF A REACTION, TRANSFORMING EVERY EXPERIENCE, WHETHER IT BE MONDAY MORNING, THE SCHOOL RUN, HOURS SPENT IN TRAFFIC OR A FRANTIC CALL TO PICK UP BREAD, INTO SOMETHING EXCITING. LET'S ENJOY EVEN THE MOST MUNDANE OF ROUTES AND MAKE OUR JOURNEY THE HIGHLIGHT OF THE DAY.







- HIGHER-PERFORMANCE HPE 500 ENGINE
- WINDSHIELD WITH INTEGRATED HAND GUARDS
- REAR GAS SHOCKS BY KAYABA
- ABS/ASR SYSTEM AND COMBINED BRAKING
- RIDE BY WIRE ELECTRONIC THROTTLE AND DOUBLE STD/ECO MAPPING
- STORAGE COMPARTMENT WITH USB PORT
- HELMET COMPARTMENT LARGE ENOUGH TO HOLD 2 FULL-FACE HELMETS
- KICKSTANDLESS PARKING SYSTEM

- SADDLE-OPENING REMOTE CONTROL WITH BIKE FINDER
- FRONT WAVE BRAKE DISCS
- CARBON LOOK FINISH
- RIDER'S FOOTPEG WITH METAL INSERTS
- MOTORCYCLE LICENSE IS REQUIRED
- NEW BRAKE PEDAL POSITION
- INCREASE IN TANK CAPACITY









- ABS/ASR SYSTEM
- SPACIOUS UNDERSEAT STORAGE COMPARTMENT WITH CAPACITY FOR TWO JET HELMETS
- RICH AND PAINSTAKINGLY CRAFTED TRIMS
- REFINED, SPORTY STYLE WITH SMOKED TOP FAIRING (ON 350 CC)

- GREAT STABILITY AND RIDING EASE IN TRAFFIC
- USB SOCKET IN THE STORAGE COMPARTMENT
- BIKE FINDER WITH REMOTE CONTROL TO SADDLE AND INDICATORS
- GREY COLOR ONLY AVAILABLE IN CANADA



LIBERTY

150 i-get - 50 i-get





- DASHBOARD WITH LCD DISPLAY
- ABS SYSTEM AT THE FRONT WHEEL ONLY ON 150 CC
- AIR-COOLED I-GET ENGINES EQUIPPED, FOR ALL ENGINE CAPACITIES, WITH ELECTRONIC INJECTION AND 3 VALVES
- LOW SADDLE UNDERSEAT COMPARTMENT WHICH CAN HOLD A JET HELMET WITH VISOR
- FRONT COMPARTMENT FOR STORAGE OF SMALL ITEMS
- LOWER SEAT TO SUIT ALL RIDERS
 AND FOLD-AWAY PASSENGER FOOTPEGS

*USA color displayed



TYPHOON

50 2S - 125 cc



- DASHBOARD WITH ANALOGUE AND DIGITAL INSTRUMENTATION
- USB PORT IN THE STORAGE COMPARTMENT
- COMPACT DIMENSIONS AND FLAT FOOTBOARD
- SPACIOUS LINDERSEAT COMPARTMENT LARGE FNOLIGH TO HOLD A FULL-FACE HELMET
- WIDE TIDES

*Thypoon 125 cc nly available in USA



MP3

- 50 litre top box
- 37 litre top box
- Quick-release thermo-formed top-box
- Thermo-formed, quick-release suitcases
- Tunnel bag
- Style windshield
- Comfort+ leg cover
- Leg cover
- Leg cover heating kit
- Heated hand grips
- Hand warmers
- Electronic anti-theft device
- Saddle-handlebar top mechanical anti-theft device
- Outdoor vehicle protection cover
- Piaggio Multimedia Platform 2.0
- Multimedia and GPS support
- Smartphone support
- Comfort+ saddle
- Comfort gel saddle
- Special Sport shock absorbers
- Carbonskin helmet with visor and retractable sun visor
- Modular helmet with visor and retractable sun visor

LIBERTY

- Windshield
- Transparent or smoked top fairing
- Top box (can hold a full-face helmet or two P-Style Jet helmets)
- Top box backrest to match the saddle
- Top box bracket kit
- Leg cover
- Outdoor vehicle cover
- Saddle-handlebar anti-theft system
- Electronic alarm
- PMP Piaggio Multimedia Platform
- Bike finder
- USB port kit
- Side stand
- Rubber mat
- P-Style helmet to match the vehicle

TYPHOON

- Windscreen
- Saddle-handlebar anti-theft system

FOR ALL VEHICLES

TomTom VIO GPS navigation system Piaggio Group special edition

BV

- Windscreen
- 37 litre top box
- 36 litre top box
- Leg cover
- Outdoor vehicle cover
- Indoor vehicle cover
- Electronic alarm
- system
- Carbonskin helmet with visor and retractable sun visor





	MP3 Sport
	500 hpe
Engine	Single cylinder hpe, 4-stroke
Engine capacity	493 сс
Bore x Stroke	94 mm x 71 mm
Power	32.5 kW (44.2 HP) a 7,750 rpm
Torque	35 ft-lbs @ 5,500 rpm
Consumption (WMTC)	58.8 mpg
CO ₂ Emissions	92 g/km
Distribution	4-Valve single overhead camshaft (sohc)
Fuel system	Ride by wire, double mapping (eco and std)
Cooling	Liquid
Lubrication	Wet sump
Starter	Electric
Gearbox	CVT with torque server
Clutch	Automatic, centrifugal dry clutch
Frame	Double cradle in high strength tubular steel
Front suspension	Articulated quadrilateral. Hydraulic suspension locking system, stroke 85 mm
Rear suspension	Double shock absorber, 4 preload position adjustment (two gas shock absorbers with continuous adjustable preload on Sport version), stroke 108 mm
Front brake	Double disc Ø 258 mm
Rear brake	Ø 240 mm disc
Front tire	Tubeless 110/70 - 13"
Rear tire	Tubeless 140/70 - 14"
Braking system	Combined braking with ABS, ASR
Length/Width/ Wheelbase	7.2' / 2.6' / 5.05'
Seat height	2.6 ft
Fuel tank capacity	3.17 gallons
Emissions compliance	Euro 4

^{*} MP3 can also be ridden with a car driver's licence, in accordance with European directive 2006/126/CE, as long as the rider is at least 21 years of age, is riding in his/her home country and respects any additional national legislation. Ask your local dealer about the specific requirements in your country.

	BV
	350 ie
Engine	Single cylinder 4-stroke
Engine capacity	330 сс
Bore x Stroke	78 mm x 69 mm
Power	22.2 kW (30.2 HP) at 8,250 rpm
Torque	21.38 ft-lbs @ 6,250 rpm
Fuel system	Electronic injection
Consumption (WMTC)	65.4 mpg
CO ₂ Emissions	85 g/km
Distribution	4-valve single overhead camshaft (sohc)
Cooling	Liquid
Lubrication	Dry sump
Starter	Electric
Gearbox	Cvt continuously variable transmission
Clutch	Oil bath automatic centrifugal multi-disk
Frame	Double cradle in high strength tubular steel
Front suspension	Hydraulic telescopic fork
Rear suspension	Dual hydraulic shock absorbers Adjustable in preload
Front brake	300 mm ø disc with hydraulic control
Rear brake	240 mm ø disc with hydraulic control
Braking system	abs/asr
Front tire	Tubeless 110/70 - 16"
Rear tire	Tubeless 150/70 - 14"
Length / Width / Wheelbase	7.18' / 2.56' / 5.12'
Saddle height	2.6 ft
Fuel tank capacity	3.3 gallons
Emissions compliance	Euro 4

	LIBERTY	
	150 i-get	50 i-get
Engine	Single cylinder 4-stroke i-get	single cylinder 4-stroke i-get
Engine capacity	155 cc	49.9 сс
Bore x Stroke	58 mm x 58.6 mm	39 mm x 41.8 mm
Power	9.6 kW (13 HP) a 7,750 rpm	2.4 kW (3.3 HP) a 7,500 rpm
Torque	9.58 ft-lbs @ 5,250 rpm	2.28 ft-lbs @ 7,250rpm
Consumption (WMTC)	86.5 mpg	83.9 mpg
CO ₂ Emissions	65 g/Km	62 g/km
Distribution	Single overhead camshaft, 3 valves (2 intake, 1 exhaust)	Single overhead camshaft, 3 valves (2 intake, 1 exhaust)
Cooling	Air	Air
Lubrication	Oil with wet sump	Oil with wet sump
Fuel system	Electronic injection	Electronic injection
Starter	Electric	Electric
Gearbox	Automatic CVT	Automatic CVT
Clutch	Automatic centrifugal dry clutch	Automatic centrifugal dry clutch
Frame	High resistance tubular steel	High resistance tubular steel
Front suspension	Telescopic hydraulic fork, 76 mm stroke	Telescopic hydraulic fork, 76 mm stroke
Rear suspension	Single hydraulic shock absorber with 5-position preload adjustment, 74.5 mm stroke	Single hydraulic shock absorber, 73.5 mm stroke
Front tire	Tubeless 90 / 80 - 16", 51J	Tubeless 90 / 80 - 16", 51J
Rear tire	Tubeless 100 / 80 - 14", 54J	Tubeless 100 / 80 - 14", 54J
Front brake	Single Ø 240 mm disc	Single Ø 240 mm disc
Rear brake	Ø 140 mm drum	Ø 140 mm drum
ABS	ABS at the front wheel only	
Length/ Width/Wheelbase	6.38' / 2.26' / 4.39'	6.38' / 2.26' / 4.49'
Seat height	<2.59ft	2.55ft
Fuel tank capacity	1.58 gallons	1.58 gallons
Emissions compliance	EURO 4	EURO 4

	TYPHOON	
	50 2S 4 stroke	125 cc
Engine	Single cylinder 4-stroke	Single cylinder 4-stroke 2 valves
Engine capacity	49 cc	124 cc
Bore per stroke	40 mm x 39.3 mm	57 mm x 48.6 mm
Power	3 HP @ 7,000 rpm	9.3 HP @ 8,500 rpm
Torque	2.21 ft-lbs @ 6,500 rpm	6 ft-lbs @ 7,500 rpm
Consumption (WMTC)	61.8 mpg	TBD
CO ₂ Emissions	85 g/km CO2	TBD
Cooling	Air	Air
Lubrication	Automatic mixer	Wet sump
Fuel system	Electronic carburetor	Electronic injection
Starter	Electronic starter and kick start	Electric
Gearbox	Automatic CVT	CVT with torque server
Clutch	Automatic centrifugal dry clutch	Automatic centrifugal dry clutch
Frame	Single cradle structure in high resistance tubular steel	Single cradle structure in tubular steel with pressed reinforcements
Front suspension	Hydraulic telescopic fork	Hydraulic telescopic fork
Rear suspension	Single hydraulic shock absorber	Hydraulic single shock absorber with spring preload
Front tire	120/80 - 12"	120/80 - 12"
Rear tire	130/80 - 12"	130/80 - 12"
Front brake	220 mm Ø disc	220 mm Ø disc w/ hydraulic control
Rear brake	140 mm Ø drum	Ø 140 mm drum
Length / Width / Wheelbase	6.38' / 2.26' / 4.46'	6.38' / 2.26' / 4.46'
Seat Height	31.06 in	31.06 in
Fuel tank capacity	1.7 gallons	1.7 gallons
Emissions compliance	EURO 4	EURO 4

The company reserves the right to make technical and aesthetic modifications at any time. Complete information regarding models and accessories is available at www.piaggio.com. Ride carefully, always wearing a helmet and suitable gear. Always comply with the Highway Code and respect the environment. Read the user and maintenance manuals thoroughly. Always request original, homologated spare parts in accordance with the laws in force. Refer to Official Piaggio Dealers and Authorised Retailers for a secure purchase and guaranteed customer service.

=ISO 9001=

COMPANY WITH COMPANY WITH COMPANY WITH QUALITY SYSTEM ENVIRONMENTAL SYSTEM CERTIFIED BY DNV CERTIFIED BY DNV =ISO 14001=

Piaggio is a registered trademark of Piaggio & C. S.p.A.

DEALERSHIP STAMP

